



SERIES NO. H1W **QUANTITY**

STANDARD FEATURES:

- 1/4 ALUMINUM TREAD PLATE COVER
- 1/4 THICK ALUMINUM FRAME EXTRUSION
- T-316 STAINLESS STEEL HARDWARE
- S.STL. & ALUM. HOLD OPEN ARM
- S.STL. SPRING ASSIST
- 1 1/2" DRAIN COUPLING
- RECESSED LIFT HANDLE (S)
- S.STL. SLAM LOCK W/ KEY
- LIFETIME WARRANTY
- H-20 LOAD RATING

OPTIONS / FEATURES

- PADLOCK BAR
- KEYED CYLINDER LOCK
- RECESSED LOCK BOX
- CLEAR ANODIZED FINISH
- LACQUER FINISH
- BITUMINUS COATING
- GASKET / CUSHION
- 3" INSULATION W/ CAPTIVE PAN
- BOLT DOWN COVER
- SAFETY CABLE W/ POST
- PVC PROTECTIVE COVER
- NUTRIL - SPECIFY LOCATION BELOW

LOCATION

SLAB SKIRT OVERALL HEIGHT
 (INCLUDING FRAME)

NOTE:

- 1) SUITABLE FOR USE IN OFF STREET LOCATION WHERE NOT SUBJECTED TO TRAFFIC.
- 2) PROVIDE A FULL BED OF CLASS "A" CONCRETE UNDER FRAME AND SUPPORT ANGLES.

TAG / NOTES