

SERIES W1C ACCESS DOOR



www.HallidayProducts.com
 Phone: (800) 298-1027
 Local: (407) 298-4470
 Sales@HallidayProducts.com

STANDARD FEATURES:

- 300 LBS. PER SQ. FT. LOAD RATING (1464 KG PER SQ. METER LOAD RATING)
- EXTRUDED ALUMINUM CHANNEL FRAME
- SINGLE LEAF CONSTRUCTION
- AUTO-LOCK T-316 STAINLESS STEEL HOLD OPEN ARM WITH RELEASE HANDLE
- T-316 STAINLESS STEEL HINGES AND ATTACHING HARDWARE
- T-316 STAINLESS STEEL SLAM LOCK WITH REMOVABLE KEY
- STAINLESS STEEL COMPRESSION SPRING ASSIST
- BUILT-IN EPDM CUSHION/GASKET
- NON-OZONE DEPLETING BITUMINOUS COATING
- RECESSED LIFTING HANDLE
- LIFETIME GUARANTEE

STANDARD SIZES

QTY.	MODEL NO.	A DIM INCHES (MM)	C DIM INCHES (MM)	UNIT WT. LBS. (KG)
	W1C2424	24 (610)	24 (610)	57 (26)
	W1C2430	24 (610)	30 (762)	64 (29)
	W1C2436	24 (610)	36 (914)	72 (33)
	W1C2442	24 (610)	42 (1067)	80 (36)
	W1C2448	24 (610)	48 (1219)	88 (40)
	W1C3030	30 (762)	30 (762)	73 (33)
	W1C3036	30 (762)	36 (914)	82 (37)
	W1C3042	30 (762)	42 (1067)	90 (41)
	W1C3048	30 (762)	48 (1219)	100 (45)
	W1C3054	30 (762)	54 (1372)	108 (49)
	W1C3060	30 (762)	60 (1524)	116 (53)
	W1C3636	36 (914)	36 (914)	91 (41)
	W1C3642	36 (914)	42 (1067)	101 (46)
	W1C3648	36 (914)	48 (1219)	111 (50)
	W1C3654	36 (914)	54 (1372)	120 (54)
	W1C3660	36 (914)	60 (1524)	130 (59)
	W1C3666	36 (914)	66 (1676)	140 (64)
	W1C3672	36 (914)	72 (1829)	150 (68)
	W1C4242	42 (1067)	42 (1067)	113 (51)

