

SERIES W2C ACCESS DOOR



www.HallidayProducts.com
 Phone: (800) 298-1027
 Local: (407) 298-4470
 Sales@HallidayProducts.com

STANDARD FEATURES:

- 300 LBS. PER SQ. FT. LOAD RATING (1464 KG PER SQ. METER LOAD RATING)
- EXTRUDED ALUMINUM CHANNEL FRAME
- DOUBLE LEAF CONSTRUCTION
- AUTO-LOCK T-316 STAINLESS STEEL HOLD OPEN ARM WITH RELEASE HANDLE
- T-316 STAINLESS STEEL HINGES AND ATTACHING HARDWARE
- T-316 STAINLESS STEEL SLAM LOCK WITH REMOVABLE KEY
- STAINLESS STEEL COMPRESSION SPRING ASSIST
- BUILT-IN EPDM CUSHION/GASKET
- NON-OZONE DEPLETING BITUMINOUS COATING
- RECESSED LIFTING HANDLE
- LIFETIME GUARANTEE

STANDARD SIZES

QTY.	MODEL NO.	A DIM INCHES (MM)	C DIM INCHES (MM)	UNIT WT. LBS. (KG)
	W2C4242	42 (1067)	42 (1067)	119 (54)
	W2C4842	48 (1219)	42 (1067)	130 (59)
	W2C4848	48 (1219)	48 (1219)	142 (64)
	W2C5442	54 (1372)	42 (1067)	141 (64)
	W2C5448	54 (1372)	48 (1219)	154 (70)
	W2C5454	54 (1372)	54 (1372)	166 (75)
	W2C6030	60 (1524)	30 (762)	122 (55)
	W2C6036	60 (1524)	36 (914)	135 (61)
	W2C6042	60 (1524)	42 (1067)	151 (68)
	W2C6048	60 (1524)	48 (1219)	165 (75)
	W2C6054	60 (1524)	54 (1372)	179 (81)
	W2C6060	60 (1524)	60 (1524)	195 (88)
	W2C6636	66 (1676)	36 (914)	145 (66)
	W2C6648	66 (1676)	48 (1219)	177 (80)
	W2C7236	72 (1829)	36 (914)	154 (70)
	W2C7242	72 (1829)	42 (1067)	173 (78)
	W2C7248	72 (1829)	48 (1219)	188 (85)
	W2C7254	72 (1829)	54 (1372)	204 (92)
	W2C7260	72 (1829)	60 (1524)	222 (101)

